



CERTIFICATE
NR 615/41/OA/06/2012/A
OF PRODUCT COMPLIANCE
WITH REQUIREMENTS OF STRENGTH
AND DURABILITY

It is stated that according to the results of executed tests

ball bearing slides PUSH TO OPEN 45 mm L 300 mm – 600 mm

distributed by

GTV sp. z o.o. sp. k.
ul. Przejazdowa 21 05-800 Pruszków

meets the following requirements:

PN-EN 15338 + A1:2010 /EN 15338:2007 + A1:2010 Hardware for furniture – Strength and durability of extension elements and their component - IDT /.

Tests conducted according to

EN 15338:2007 + A1:2010, points 4 - 6.3.13, according 3 /highest/ test level.

Tests were executed: 28.05.2012 – 14.06.2012

The Certificate contains test report /2 numbered pages/, which are an integral part of the Certificate.

**Engineering Centre For Creating
Product Quality „ATEST” Ltd
str. Bogusławskiego 16, 60-214 Poznań
tel. 61 - 8 652 689
Laboratory in Gruszczyń / Poznań
ul. Leśna 12 62-006 Kobylnica**


Signed for and on behalf
“ATEST” Ltd”

DIRECTOR

mgr inż. Lucjan Kokorniak

Poznań, 14.06.2012






**ENGINEERING CENTRE FOR CREATING
PRODUCT QUALITY**
„ATEST” Ltd

Test report number 615/41/OA/06/2012/A

Page 1

Article tested: ball bearing slides PUSH TO OPEN 45 mm L = 300 mm

PN-EN 15338 + A1:2010 /EN 15338:2007 + A1:2010 Hardware for furniture – Strength and durability of extension elements and their component - IDT /.			
Point of standard		Parameters of test	Test result
6.2 Overload test – the first set			
6.2.2	Vertical downwards static overload	vertical force 300 N, 10 times	pass, the extension element did not detach
6.2.3	Horizontal sideways static overload	horizontal force 150 N, 5 times	pass, the extension element did not detach
6.2.4	Outwards static overload	horizontal force 200 N	the extension element did not detach
6.2.5	Slam–shut/open	1,0 m/s, 10 times	pass, the extension element did not detach
6.3 Functional tests – the second set			
6.3.4	Operating forces	force < 50 N	pass, the extension element fulfils its function
6.3.5	1 vertical downwards static load test	vertical force 200 N, 10 times	pass, the extension element fulfils its function
6.3.6	1 horizontal sideways static load	horizontal force 100 N, 5 times	pass, the extension element fulfils its function
6.3.8	Durability	60 000 cycles	pass, the extension element and opening mechanism fulfils its function
6.3.9	Deflection of front	2,0 mm	pass, < 4 %
6.3.10	2 vertical downwards static load	vertical force 200 N, 10 times	pass, the extension element fulfils its function
6.3.11	2 horizontal sideways static load	horizontal force 100 N, 5 times	pass, the extension element fulfils its function
6.3.12	Operating forces	force < 50 N	pass, the extension element fulfils its function
6.3.13	Slam–shut/open	0,5 m/s, 10 times	pass, the extension element fulfils its function



**ENGINEERING CENTRE FOR CREATING
PRODUCT QUALITY**
„ATEST” Ltd

Test report number 615/41/OA/06/2012/A

Page 2

Article tested: ball bearing slides PUSH TO OPEN 45 mm L = 600 mm

PN-EN 15338 + A1:2010 /EN 15338:2007 + A1:2010 Hardware for furniture – Strength and durability of extension elements and their component - IDT /.			
Point of standard		Parameters of test	Test result
6.2 Overload test – the first set			
6.2.2	Vertical downwards static overload	vertical force 300 N, 10 times	pass, the extension element did not detach
6.2.3	Horizontal sideways static overload	horizontal force 150 N, 5 times	pass, the extension element did not detach
6.2.4	Outwards static overload	horizontal force 200 N	the extension element did not detach
6.2.5	Slam–shut/open	1,3 m/s, 10 times	pass, the extension element did not detach
6.3 Functional tests – the second set			
6.3.4	Operating forces	force < 50 N	pass, the extension element fulfils its function
6.3.5	1 vertical downwards static load test	vertical force 200 N, 10 times	pass, the extension element fulfils its function
6.3.6	1 horizontal sideways static load	horizontal force 100 N, 5 times	pass, the extension element fulfils its function
6.3.8	Durability	60 000 cycles	pass, the extension element and opening mechanism fulfils its function
6.3.9	Deflection of front	3,1 mm	pass, < 4 %
6.3.10	2 vertical downwards static load	vertical force 200 N, 10 times	pass, the extension element fulfils its function
6.3.11	2 horizontal sideways static load	horizontal force 100 N, 5 times	pass, the extension element fulfils its function
6.3.12	Operating forces	force < 50 N	pass, the extension element fulfils its function
6.3.13	Slam–shut/open	0,8 m/s, 10 times	pass, the extension element fulfils its function

Maximal loading capacity drawers with ball bearing slides PUSH TO OPEN 45 mm

M = 30 kg.

INŻYNIERSKI OŚRODEK
KSZTAŁTOWANIA JAKOŚCI WYROBÓW
„ATEST” Spółka z o.o.
60-214 Poznań, ul. Bogusławskiego 16
tel./fax (061) 865-26-89
NIP 779-205-14-74, Regon 630681995

PREZES

mgr inż. Łucjan Kokorniak